



No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180700666701
Page: 1 of 20

TEST REPORT

Application No.: SZEM1807006667BA
Applicant: Flashbay Electronics
Address of Applicant: Bldg. NO.1 101~501, Bldg. NO.2, Bldg. NO. 3 1~4F, Xifengcheng Industrial Park, No. 2 Fuyuan Rd, Heping, Fuhai, Bao'an District, Shenzhen City · Guangdong Province, P.R. China
Manufacturer/ Factory: Flashbay Electronics
Address of Manufacturer/ Factory: Bldg. NO.1 101~501, Bldg. NO.2, Bldg. NO. 3 1~4F, Xifengcheng Industrial Park, No. 2 Fuyuan Rd, Heping, Fuhai, Bao'an District, Shenzhen City · Guangdong Province, P.R. China

Equipment Under Test (EUT):

EUT Name: Power banks
Model No.: BigBoost
Standard(s) : VCCI-CISPR 32:2016
Date of Receipt: 2018-07-25
Date of Test: 2018-07-26 to 2018-07-30
Date of Issue: 2018-08-01

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.





Keny Xu
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2018-08-01		Original

Authorized for issue by:				
				
		<hr/>		
		Foray Chen /Project Engineer		
				
		<hr/>		
		Eric Fu /Reviewer		



2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	VCCI-CISPR 32:2016	VCCI-CISPR 32:2016	Class B	Pass
Radiated Emissions (30MHz-1GHz)	VCCI-CISPR 32:2016	VCCI-CISPR 32:2016	Class B	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION.....	6
4.5 TEST FACILITY.....	6
4.6 DEVIATION FROM STANDARDS.....	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST	7
6 EMISSION TEST RESULTS	8
6.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz)	8
6.1.1 <i>E.U.T. Operation</i>	8
6.1.2 <i>Test Setup Diagram</i>	8
6.1.3 <i>Measurement Data</i>	8
6.2 RADIATED EMISSIONS (30MHz-1GHz).....	11
6.2.1 <i>E.U.T. Operation</i>	11
6.2.2 <i>Test Setup Diagram</i>	11
6.2.3 <i>Measurement Data</i>	11
7 PHOTOGRAPHS	14
7.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz) TEST SETUP	14
7.2 RADIATED EMISSIONS (30MHz-1GHz) TEST SETUP	14
7.3 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	15-20

4 General Information

4.1 Details of E.U.T.

Power supply:	Input: DC5V 1A Output: DC5V 1A Rechargeable battery: 10050mAh 37.2Wh
Cable:	USB cable: 10cm unshielded Micro USB cable: 10cm unshielded

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1357 W010A051	REF. No.SEA0500
iPhone 6	Apple	MG472ZP/A	C34NHTMFG5MN
Load Resistor	SGS	N/A	REF. No.SEA0600
Mobile Phone	LeTV	Le X620	LP031262A6180395427
USB Cable	PHILIPS	SWR2101	REF. No.SEA0700

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction Emission	± 3.0dB (150kHz to 30MHz)
2	Radiated Emission	± 4.5dB (30MHz-1GHz)
3	Temperature test	± 1 °C
4	Humidity test	± 3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2017-05-10	2020-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2018-07-12	2019-07-11
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2018-04-02	2019-04-01
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018-04-02	2019-04-01

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2018-03-31	2021-03-30
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2018-07-12	2019-07-11
EMI Test Receiver (9kHz-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2018-04-02	2019-04-01
Trilog-Broadband Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2018-04-13	2019-04-12

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07

6 Emission Test Results

6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement:	VCCI-CISPR 32:2016
Test Method:	VCCI-CISPR 32:2016
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

6.1.1 E.U.T. Operation


Operating Environment:

Temperature: 20.6 °C Humidity: 50.4 % RH Atmospheric Pressure: 1005 mbar

Pretest these modes to find the worst case:
 a: Charge mode, keep EUT being charged with adapter.
 c: Charge and discharge mode, keep EUT being charged with adapter and working with full load.

The worst case for final test:
 a: Charge mode, keep EUT being charged with adapter.


6.1.2 Test Setup Diagram



6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.

Mode:a; Line:Live Line




Site : Shielding Room
 Condition: Line
 Job No. : 06667BA
 Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.18	0.03	9.51	31.52	41.06	54.59	-13.53	Average
2	0.18	0.03	9.51	38.00	47.54	64.59	-17.05	QP
3	0.26	0.03	9.51	23.20	32.74	51.42	-18.68	Average
4	0.26	0.03	9.51	31.73	41.27	61.42	-20.15	QP
5	0.33	0.03	9.50	18.39	27.92	49.57	-21.65	Average
6	0.33	0.03	9.50	28.31	37.84	59.57	-21.73	QP
7	0.50	0.04	9.49	20.28	29.81	46.00	-16.19	Average
8	0.50	0.04	9.49	29.14	38.67	56.00	-17.33	QP
9	0.67	0.07	9.50	17.30	26.87	46.00	-19.13	Average
10	0.67	0.07	9.50	27.45	37.02	56.00	-18.98	QP
11	1.45	0.13	9.51	13.30	22.94	46.00	-23.06	Average
12	1.45	0.13	9.51	23.27	32.91	56.00	-23.09	QP



Mode:a; Line:Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 06667BA
Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Limit	Over	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.17	0.03	9.59	30.69	54.72	-14.41	Average
2	0.17	0.03	9.59	37.51	64.72	-17.59	QP
3	0.34	0.03	9.58	23.22	49.27	-16.44	Average
4	0.34	0.03	9.58	28.99	59.27	-20.67	QP
5	0.51	0.04	9.60	23.91	46.00	-12.45	Average
6	0.51	0.04	9.60	30.59	56.00	-15.77	QP
7	0.59	0.06	9.62	20.77	46.00	-15.55	Average
8	0.59	0.06	9.62	26.43	56.00	-19.89	QP
9	0.67	0.07	9.62	21.24	46.00	-15.07	Average
10	0.67	0.07	9.62	28.95	56.00	-17.36	QP
11	0.78	0.07	9.61	18.48	46.00	-17.84	Average
12	0.78	0.07	9.61	26.67	56.00	-19.65	QP

6.2 Radiated Emissions (30MHz-1GHz)

Test Requirement:	VCCI-CISPR 32:2016
Test Method:	VCCI-CISPR 32:2016
Frequency Range:	30MHz to 1GHz
Measurement Distance:	10m
Limit:	
30MHz-230MHz	30 dB(μV/m) quasi-peak
230MHz-1GHz	37 dB(μV/m) quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to 1000MHz

6.2.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 51 % RH Atmospheric Pressure: 1005 mbar

Pretest these modes to find the worst case:

- a: Charge mode, keep EUT being charged with adapter.
- b: Discharge mode, keep EUT working with full load.
- c: Charge and discharge mode, keep EUT being charged with adapter and working with full load.
- d: Idle mode.

The worst case for final test: c: Charge and discharge mode, keep EUT being charged with adapter and working with full load.

6.2.2 Test Setup Diagram




6.2.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:c; Polarization:Horizontal




Condition: 10m HORIZONTAL
Job No. : 06667BA
Test Mode: c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	36.90	6.79	12.91	32.47	27.41	30.00	-15.36
2	48.84	6.90	12.81	32.45	27.51	30.00	-15.23
3 pp	125.45	7.33	11.79	32.45	35.80	30.00	-7.53
4	185.14	7.57	10.33	32.41	32.26	30.00	-12.25
5	237.48	7.79	11.00	32.38	34.42	37.00	-16.17
6	965.54	9.55	22.78	31.04	26.28	37.00	-9.43



Mode:c; Polarization:Vertical



Condition: 10m VERTICAL
Job No. : 06667BA
Test Mode: c


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	57.80	7.00	12.16	32.45	35.46	30.00	-7.83
2	92.79	7.19	8.89	32.47	35.57	30.00	-10.82
3	114.51	7.27	10.89	32.46	38.88	30.00	-5.42
4 pp	121.55	7.31	11.58	32.45	38.31	30.00	-5.25
5	186.44	7.58	10.19	32.41	35.10	30.00	-9.54
6	945.44	9.53	22.70	31.21	27.40	37.00	-8.58

7 Photographs

7.1 Conducted Emissions at Mains Terminals (150kHz-30MHz) Test Setup




7.2 Radiated Emissions (30MHz-1GHz) Test Setup







7.3 EUT Constructional Details (EUT Photos)














- End of the Report -